

**BEFORE THE BOARD OF PATENT APPEALS AND INTERFERENCES  
IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re the Application of:

Group Art Unit: 2644

**Jon C. Taenzer**

Examiner: Ping Lee

**Serial No.:** 10/812,718

**Filed:** March 29, 2004

**For: HEARING SYSTEM  
BEAMFORMER**

**APPEAL BRIEF UNDER 37 CFR § 41.37**

## Mail Stop Appeal Brief - Patents

Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

In response to the Notice of Non-Compliant Appeal Brief, Applicant hereby submits a revised Appeal Brief to address the alleged deficiency. Applicant submits this Appeal Brief pursuant to the Notice of Appeal filed May 23, 2006. This brief is submitted in triplicate.

|                                     |                   |
|-------------------------------------|-------------------|
| Real Party in Interest              | begins on page 2  |
| Related Appeals and Interferences   | begins on page 2  |
| Status of Claims,                   | begins on page 2  |
| Status of Amendments                | begins on page 2  |
| Summary of Claimed Subject Matter   | begins on page 2  |
| Grounds of Rejection to be reviewed | begins on page 4  |
| Arguments                           | begins on page 4  |
| Conclusion                          | begins on page 8  |
| Appendix A – Appealed Claims        | begins on page 9  |
| Evidence Appendix                   | begins on page 12 |
| Related Preceding Appendix          | begins on page 13 |

**I. REAL PARTY IN INTEREST**

The real party in interest is the assignee GN Resound North America Corporation.

**II. RELATED APPEALS AND INTERFERENCES**

To the best of Applicant's knowledge, there are no related appeals or interferences.

**III. STATUS OF CLAIMS**

Claims 1-16 and 36-52 were canceled. Claims 17-35 are pending. Claims 17-35 are rejected, and are appealed. Claims 17 and 23 are independent claims.

**IV. STATUS OF AMENDMENTS**

Amendment After Final under 37 C.F.R. § 1.116 was filed on February 28, 2006, in which claims 36-52 were canceled. The amendments to the claims were entered according to the Advisory Action mailed on March 15, 2006.

**V. SUMMARY OF CLAIMED SUBJECT MATTER**

The present section of the Appeal Brief is set forth merely to comply with the requirements of 37 C.F.R. § 41.37(c)(v) and is not intended to limit the pending claims in any way.

Claim 17 recites:

A method of achieving directional pickup of a radiated energy signal using a shadowing effect created by an energy propagation barrier, the method comprising:

locating a first sensor on one side of the barrier and a second sensor on an opposite side of the barrier;

determining a difference between amplitudes of signals respectively produced by the first and second sensors;

adjusting the amplitudes of the signals based on the determined amplitude difference to produce adjusted signals; and

summing together the adjusted signals to produce a directional signal.

Claim 23 recites:

Apparatus for achieving directional pickup of a radiated energy signal using a shadowing effect created by an energy propagation barrier, the apparatus comprising:

a first sensor configured for being located on one side of the barrier;

a second sensor configured for being located on an opposite side of the barrier;

processing circuitry configured for determining a difference between the amplitudes of signals respectively produced by the first and second sensors, for adjusting the amplitudes of the signals based on the determined amplitude difference to produce adjusted signals; and for summing together the adjusted signals to produce a directional signal.

Examples of a method that includes locating a first sensor on one side of the barrier and a second sensor on an opposite side of the barrier, determining a difference between amplitudes of signals respectively produced by the first and second sensors, adjusting the amplitudes of the signals based on the determined amplitude difference to produce adjusted signals, and summing together the adjusted signals to produce a directional signal, are described on pages 5-17 of the specification.

Examples of an apparatus for achieving directional pickup of a radiated energy signal using a shadowing effect created by an energy propagation barrier, having a first sensor configured for being located on one side of the barrier, a second sensor configured for being located on an opposite side of the barrier, and processing circuitry configured for determining a difference between the amplitudes of signals respectively produced by the first and second sensors, for adjusting the amplitudes of the signals based on the determined amplitude difference to produce adjusted signals, and for summing together the adjusted signals to produce a directional signal, are described on pages 5-17 of the specification.

In particular, with respect to embodiments covered by claims 17 and 23, figures 2, 7, 8, 9 discloses left and right sensors for generating respective signals, wherein the sensors are adapted to be placed on either side of a head (barrier). Also, page 15, lines 18-21 disclose amplitude difference between right ear and left ear signals in relation to head shadowing effect, page 15, lines 5-14 discloses beamforming technique based on head shadowing effect to optimize signal-to-noise ratio and adjusting amplitudes in a beamformer embodiment, and figures 15, 16, 19, and 20 and page 16, line 19 to page 17, line 23 disclose interaural difference, and adjusting signals based on the interaural difference. Also, figures 2, 7, 8, 9 illustrates a summer for summing signals to produce a directional signal.

## **VI. GROUNDS OF REJECTION TO BE REVIEWED ON APPEAL**

The grounds of rejection to be reviewed on appeal are follow: Claims 17-52 are rejected under 35 U.S.C. § 112 for allegedly failing to comply with the written description requirement. Claims 17, 19-21, 23, 25-27, 36, 46, and 47 are allegedly patentable under 35 U.S.C. § 102(b) over “Microphone-Array Hearing Aids with Binaural Output - Part II: A Two-Microphone Adaptive System” by Daniel P. Welker (“Welker”). Claims 17, 18, 23, 24, 36, 42-45, and 49-52 are allegedly patentable under 35 U.S.C. 103(a) over U.S. Patent No. 6,697,494 (“Klootsema”).

## **VII. ARGUMENTS**

Claims 18-22 and 29-32 depend from independent claim 17, and therefore, rise and fall with claim 17. Claims 24-28 and 33-35 depend from independent claim 23, and therefore, rise and fall with claim 23.

### **A. Claim Rejections under 35 U.S.C. § 112**

Claims 17-52 stand rejected under 35 U.S.C. § 112 as allegedly failing to comply with the written description requirement. For written description rejection under § 112, “the fundamental factual inquiry is whether the specification conveys with reasonable clarity to those skilled in the art that, as of the filing date sought, applicant was in possession of the invention as now claimed.” MPEP 2163.02. Also, the “subject matter of the claim need not be described literally (i.e., using the

same terms or in haec verba) in order for the disclosure to satisfy the description requirement.”  
MPEP 2163.02.

According to the Office Action, the specification allegedly does not disclose a difference between amplitudes of signals respectively produced by the first and second sensors, and adjusting the amplitudes of the signals based on the determined amplitude difference to produce adjusted signals, as recited in claim 17, and similarly recited in claim 23. Applicant respectfully disagree. Page 15, lines 18-21 of the application disclose amplitude difference between right ear and left ear signals in relation to head shadowing effect. In addition, page 15, lines 5-14 discuss beamforming technique based on head shadowing effect to optimize signal-to-noise ration, and adjusting amplitudes in a beamformer embodiment. Furthermore, figures 15, 16, 19, and 20, and their corresponding passages discuss interaural difference, and adjusting signals based on the interaural difference. Beamforming technique for adjusting signals is also discussed throughout the specification. As such, the specification conveys to those skilled in the art that Applicant was in possession of the claimed invention. For at least the foregoing reasons, Applicant respectfully submits that claims 17-52 satisfy 35 U.S.C. § 112.

**B. Claim Rejections under 35 U.S.C. § 102**

Applicant respectfully notes that in order to sustain a claim rejection under § 102, each of the claimed elements must be disclosed, either expressly or inherently, in the cited reference. Applicant submits that claims 17 and 23 are patentable over Welker because Welker does not disclose or suggest one or more limitations recited in these claims.

Claim 17 recites determining a difference between amplitudes of signals respectively produced by the first and second sensors, and adjusting the amplitudes of the signals based on the determined amplitude difference to produce adjusted signals. Claim 23 recites similar limitations. Welker does not disclose or suggest the above limitations. Welker discloses a microphone system, wherein signals from right and left microphones,  $f_R$  and  $f_L$ , respectively, are adjusted (See figure 2). Notably, in the top line of figure 2, signal  $f_L$  is added to signal  $f_R$ , and in the bottom line, signal  $f_L$  is subtracted from signal  $f_R$ . As such, Welker does not disclose or suggest adjusting amplitudes of

signals (e.g., both left and right signals) based on a determined amplitude difference (i.e., the same amplitude difference).

According to the Advisory Action, figure 2 of Welker allegedly discloses modifying left signal by Wk, and modifying right signal by Wk. Applicant respectfully disagree. First, Wk is not an amplitude difference. As such, even assuming that Welker discloses modifying left and right signals based on Wk (which is not true), Welker still does not disclose or suggest modifying left and right signals based on an amplitude difference. In addition, figure 2 discloses that Wk is used in a signal path for the left sensor, and that Wk is not used in the right signal path. As such, figure 2 of Welker does not disclose or suggest the above limitations.

For at least the foregoing reasons, Applicant respectfully submits that claims 17 and 23, and their respective dependent claims, are patentable over Welker under 35 U.S.C. § 102.

C. Claim Rejections under 35 U.S.C. § 103

Applicant submits that claims 17 and 23 are patentable over Klootsema.

Claim 17 recites determining a difference between amplitudes of signals respectively produced by the first and second sensors, and adjusting the amplitudes of the signals based on the determined amplitude difference to produce adjusted signals. Claim 23 recites similar limitations. Applicant agrees with the Examiner that Klootsema does not disclose or suggest determining an amplitude difference. According to the Office Action, it would have been allegedly obvious to modify Klootsema by determining an amplitude difference so that the signals may be adjusted. Applicant respectfully disagrees. Klootsema discloses matching the levels of microphone signals, and does not disclose or suggest determining an amplitude difference, and adjusting signals based on the same determined amplitude difference. Also, just because matching of signals is disclosed, it does not necessitate a finding that the matched signals are determined based on an amplitude difference. As the Examiner correctly pointed out, there are different techniques that can be used to match signals. For example, two signals may be matched by adding the two signals and taking an average, in which case, there will be no need to determine an amplitude difference. As another example, two signals may also be matched by making one equal to the other. In such case, there will also be no need to determine an amplitude difference. Furthermore, even assuming that Klootsema discloses determining amplitude difference (which is not true), there is nothing in Klootsema that

disclose or suggest adjust left signal based on the amplitude difference, and adjusting right signal based on the amplitude difference.

For at least the foregoing reasons, Applicant respectfully submits that claims 17 and 23, and their respective dependent claims, are patentable over Klootsema under 35 U.S.C. § 103.


**VIII. CONCLUSION**

For the above reasons, Applicant respectfully submits that rejection of claims 17-35 has been overcome. Accordingly, Applicant requests that the Board of Patent Appeals and Interferences overrule the Examiner and allow claims 17-35.

The Commissioner is authorized to charge any fees due or credit any overpayment in connection with the filing of this document to Bingham McCutchen's Deposit Account No. 50-4047, referencing billing number **7036165001**. If the Examiner has any questions or comments, please contact the undersigned at the number listed below.

Respectfully submitted,

Dated: August 8, 2007

By:   
Gerald Chan  
Reg. No. 51,541

BINGHAM MCCUTCHEN LLP  
Three Embarcadero Center  
San Francisco, CA 94111-4067  
Telephone: (650) 849-4960  
Telefax: (650) 849-4800



**APPENDIX A: Pending Claims**

**Listing of Appealed Claims 17-52.**

17. (Previously Presented) A method of achieving directional pickup of a radiated energy signal using a shadowing effect created by an energy propagation barrier, the method comprising:

locating a first sensor on one side of the barrier and a second sensor on an opposite side of the barrier;

determining a difference between amplitudes of signals respectively produced by the first and second sensors;

adjusting the amplitudes of the signals based on the determined amplitude difference to produce adjusted signals; and

summing together the adjusted signals to produce a directional signal.

18. (Original) The method of claim 17, wherein the adjusted signals are of approximately equal magnitude.

19. (Previously Presented) The method of claim 17, wherein the adjusted signals are summed together to produce multiple directional signals.

20. (Original) The method of claim 19, wherein the multiple directional signals form a binaural signal pair including a first directional signal in which energy from the first sensor is greater than energy from the second sensor, and a second directional signal in which energy from the second sensor is greater than energy from the first sensor.

21. (Previously Presented) The method of claim 17, further comprising, for each of multiple frequency bands:

deriving a phase correction value; and

applying the phase correction value within that frequency band.

22. (Previously Presented) The method of claim 21, wherein the amplitude difference between the signals is determined within each of the multiple frequency bands, and the phase correction value determination is based on the amplitude difference determined within the respective frequency band.

23. (Previously Presented) Apparatus for achieving directional pickup of a radiated energy signal using a shadowing effect created by an energy propagation barrier, the apparatus comprising:  
a first sensor configured for being located on one side of the barrier;  
a second sensor configured for being located on an opposite side of the barrier;  
processing circuitry configured for determining a difference between the amplitudes of signals respectively produced by the first and second sensors, for adjusting the amplitudes of the signals based on the determined amplitude difference to produce adjusted signals; and for summing together the adjusted signals to produce a directional signal.

24. (Original) The apparatus of claim 23, wherein the adjusted signals are of approximately equal magnitude.

25. (Previously Presented) The apparatus of claim 23, wherein the processing circuitry is configured for summing together the adjusted signals to produce multiple directional signals.

26. (Original) The apparatus of claim 25, wherein the multiple directional signals form a binaural signal pair including a first directional signal in which energy from the first sensor is greater than energy from the second sensor, and a second directional signal in which energy from the second sensor is greater than energy from the first sensor.

27. (Previously Presented) The apparatus of claim 23, wherein the processing circuitry is configured for, for each of multiple frequency bands, deriving a phase correction value and applying the phase correction value within that frequency band.

28. (Previously Presented) The apparatus of claim 27, wherein the processing circuitry is configured for determining the amplitude difference between the signals within each of the multiple frequency bands, and the processing circuitry is configured for deriving a phase correction value based on the amplitude difference determined within the respective frequency band.

29. (Previously Presented) The method of claim 17, wherein the energy propagation barrier is the head of a user.

30. (Previously Presented) The method of claim 17, wherein the signals are sound signals.

31. (Previously Presented) The method of claim 30, further comprising processing the directional signal to produce a resultant sound.

32. (Previously Presented) The method of claim 31, further comprising inputting the resultant sound into left and right ears of a user.

33. (Previously Presented) The apparatus of claim 23, wherein the energy propagation barrier is the head of a user.

34. (Previously Presented) The apparatus of claim 23, wherein the first and second sensors are microphones.

35. (Previously Presented) The apparatus of claim 23, wherein the processing circuitry comprises a digital signal processor (DSP).

36-52. (Canceled)

**EVIDENCE APPENDIX**

None

**RELATED PROCEEDINGS APPENDIX**

None